



is for Accessories

When it comes to accessories, no one can match CRP's extensive stock of OEM grade adapters, ball valves, fittings, pressure gauges, and quick disconnects. Many of our adapters are plated in stainless steel and all of our accessories' male ends are chamfered. You can also count on our excellent customer service staff to see to it that all of your accessories are delivered quickly each and every time.

OUR COMPLETE ACCESSORIES LINE INCLUDES:

- High Pressure Adapters
- Ball Valves
- Hose Jacketing
- Pressure Gauges
- Quick Disconnects



Adapters

When you are using CRP high pressure hose, you want to be sure that any connections you make are equally reliable. That's where CRP high pressure adapters come in. Available in both plated steel and stainless steel, CRP adapters come in a variety of fitments and insure leak free connections and optimal flow. For added convenience and value, we even sell a pre-boxed assortment containing 17 of the most popular adapters in the industry.

PLATED STEEL

HEX NIPPLE

MALE NPT PIPE TO MALE NPT PIPE, TAPERED ENDS 30° CHAMFER



PART #	SIZE	MATERIAL
HN 12	1/8" x 1/8"	Rigid Plated Steel
HN 25	1/4" x 1/4"	Rigid Plated Steel
HN 38	3/8" x 3/8"	Rigid Plated Steel
HN 50	1/2" x 1/2"	Rigid Plated Steel
HN 75	3/4" x 3/4"	Rigid Plated Steel
HN 100	1" x 1"	Rigid Plated Steel

HEX REDUCING NIPPLE

MALE NPT PIPE TO MALE NPT PIPE, TAPERED ENDS 30° CHAMFER



PART #	SIZE	MATERIAL
HRN 1225	1/8" x 1/4"	Rigid Plated Steel
HRN 2538	1/4" x 3/8"	Rigid Plated Steel
HRN 2550	1/4" x 1/2"	Rigid Plated Steel
HRN 3850	3/8" x 1/2"	Rigid Plated Steel
HRN 3875	3/8" x 3/4"	Rigid Plated Steel
HRN 5075	1/2" x 3/4"	Rigid Plated Steel
HRN 5010	1/2" x 1"	Rigid Plated Steel
HRN 7510	3/4" x 1"	Rigid Plated Steel

MALE CONNECTOR

JIC FLARE TO MALE NPT PIPE, 30° CHAMFER PIPE END



PART #	SIZE	MATERIAL
HNJ 0412	JIC#4 x 1/8"	Rigid Plated Steel
HNJ 0425	JIC#4 x 1/4"	Rigid Plated Steel
HNJ 0438	JIC#4 x 3/8"	Rigid Plated Steel
HNJ 0450	JIC#4 x 1/2"	Rigid Plated Steel
HNJ 0525	JIC#5 x 1/4"	Rigid Plated Steel
HNJ 0625	JIC#6 x 1/4"	Rigid Plated Steel
HNJ 0638	JIC#6 x 3/8"	Rigid Plated Steel
HNJ 0650	JIC#6 x 1/2"	Rigid Plated Steel
HNJ 0825	JIC#8 x 1/4"	Rigid Plated Steel
HNJ 0838	JIC#8 x 3/8"	Rigid Plated Steel
HNJ 0850	JIC#8 x 1/2"	Rigid Plated Steel
HNJ 1275	JIC#12 x 3/4"	Rigid Plated Steel
HNJ 1610	JIC#16 x 1"	Rigid Plated Steel

PIPE SWIVEL UNION

FEMALE SWIVEL TO FEMALE SWIVEL



PART #	SIZE	MATERIAL
PSU 2525	1/4" x 1/4"	Steel
PSU 3838	3/8" x 3/8"	Steel
PSU 5050	1/2" x 1/2"	Steel
PSU 7575	3/4" x 3/4"	Steel
PSU 1010	1" x 1"	Steel

CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.
TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.

HEX PIPE COUPLING

FEMALE PIPE TO FEMALE PIPE



PART #	SIZE	MATERIAL
HPC 1212	1/8" x 1/8"	Steel
HPC 1225	1/8" x 1/4"	Steel
HPC 2525	1/4" x 1/4"	Steel
HPC 2538	1/4" x 3/8"	Steel
HPC 2550	1/4" x 1/2"	Steel
HPC 3838	3/8" x 3/8"	Steel
HPC 3850	3/8" x 1/2"	Steel
HPC 5050	1/2" x 1/2"	Steel
HPC 5075	1/2" x 3/4"	Steel
HPC 7575	3/4" x 3/4"	Steel
HPC 7510	3/4" x 1"	Steel
HPC 1010	1" x 1"	Steel

PIPE ADAPTER

MALE PIPE TO FEMALE PIPE, 30° CHAMFER MALE END



PART #	SIZE	MATERIAL
PA 1212	1/8" x 1/8"	Steel
PA 1225	1/8" x 1/4"	Steel
PA 1238	1/8" x 3/8"	Steel
PA 2525	1/4" x 1/4"	Steel
PA 2538	1/4" x 3/8"	Steel
PA 2550	1/4" x 1/2"	Steel
PA 2575	1/4" x 3/4"	Steel
PA 3838	3/8" x 3/8"	Steel
PA 3850	3/8" x 1/2"	Steel
PA 3875	3/8" x 3/4"	Steel
PA 5050	1/2" x 1/2"	Steel
PA 5075	1/2" x 3/4"	Steel
PA 5010	1/2" x 1"	Steel
PA 7575	3/4" x 3/4"	Steel
PA 7510	3/4" x 1"	Steel
PA 1010	1" x 1"	Steel

HEX REDUCER BUSHING

MALE PIPE TO FEMALE PIPE, 30° CHAMFER MALE END



PART #	SIZE	MATERIAL
HRB 1225	1/8" x 1/4"	Steel
HRB 1238	1/8" x 3/8"	Steel
HRB 1250	1/8" x 1/2"	Steel
HRB 2538	1/4" x 3/8"	Steel
HRB 2550	1/4" x 1/2"	Steel
HRB 2575	1/4" x 3/4"	Steel
HRB 2510	1/4" x 1"	Steel
HRB 3850	3/8" x 1/2"	Steel
HRB 3875	3/8" x 3/4"	Steel
HRB 3810	3/8" x 1"	Steel
HRB 5075	1/2" x 3/4"	Steel
HRB 5010	1/2" x 1"	Steel
HRB 7510	3/4" x 1"	Steel

FEMALE ADAPTER UNION

FEMALE PIPE TO FEMALE SWIVEL



PART #	SIZE	MATERIAL
FA 1212	1/8" x 1/8"	Steel
FA 1225	1/8" x 1/4"	Steel
FA 2512	1/4" x 1/8"	Steel
FA 2525	1/4" x 1/4"	Steel
FA 2538	1/4" x 3/8"	Steel
FA 3825	3/8" x 1/4"	Steel
FA 3838	3/8" x 3/8"	Steel
FA 3850	3/8" x 1/2"	Steel
FA 5038	1/2" x 3/8"	Steel
FA 5050	1/2" x 1/2"	Steel
FA 5075	1/2" x 3/4"	Steel
FA 7550	3/4" x 1/2"	Steel
FA 7575	3/4" x 3/4"	Steel
FA 7510	3/4" x 1"	Steel
FA 1075	1" x 3/4"	Steel
FA 1010	1" x 1"	Steel

MALE ADAPTER UNION

FEMALE SWIVEL TO MALE NPT PIPE



PART #	SIZE	MATERIAL
MFA 1212	1/8" x 1/8"	Steel
MFA 1225	1/8" x 1/4"	Steel
MFA 2512	1/4" x 1/8"	Steel
MFA 2525	1/4" x 1/4"	Steel
MFA 2538	1/4" x 3/8"	Steel
MFA 3825	3/8" x 1/4"	Steel
MFA 3838	3/8" x 3/8"	Steel
MFA 3850	3/8" x 1/2"	Steel
MFA 5038	1/2" x 3/8"	Steel
MFA 5050	1/2" x 1/2"	Steel
MFA 5075	1/2" x 3/4"	Steel
MFA 7550	3/4" x 1/2"	Steel
MFA 7575	3/4" x 3/4"	Steel
MFA 7510	3/4" x 1"	Steel

FEMALE ADAPTER JIC

FEMALE JIC SWIVEL TO MALE NPT PIPE



PART #	SIZE	MATERIAL
FAMJ 0425	JIC#4 x 1/4"	Steel
FAMJ 0525	JIC#5 x 1/4"	Steel
FAMJ 0625	JIC#6 x 1/4"	Steel
FAMJ 0638	JIC#6 x 3/8"	Steel
FAMJ 0838	JIC#8 x 3/8"	Steel
FAMJ 0850	JIC#8 x 1/2"	Steel
FAMJ 1275	JIC#12 x 3/4"	Steel

FEMALE ADAPTER JIC

FEMALE JIC SWIVEL TO FEMALE PIPE



PART #	SIZE	MATERIAL
FAFJ 0425	JIC#4 x 1/4"	Steel
FAFJ 0625	JIC#6 x 1/4"	Steel
FAFJ 0638	JIC#6 x 3/8"	Steel
FAFJ 0650	JIC#6 x 1/2"	Steel
FAFJ 0838	JIC#8 x 3/8"	Steel
FAFJ 0850	JIC#8 x 1/2"	Steel
FAFJ 1275	JIC#12 x 3/4"	Steel

CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.
 TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.

MALE PIPE SWIVEL ELBOW

MALE NPT PIPE TO 90° FEMALE SWIVEL



PART #	SIZE	MATERIAL
MPE 2525	1/4" x 1/4"	Steel
MPE 2538	1/4" x 3/8"	Steel
MPE 3825	3/8" x 1/4"	Steel
MPE 3838	3/8" x 3/8"	Steel
MPE 3850	3/8" x 1/2"	Steel
MPE 5038	1/2" x 3/8"	Steel
MPE 5050	1/2" x 1/2"	Steel
MPE 5075	1/2" x 3/4"	Steel
MPE 7550	3/4" x 1/2"	Steel
MPE 7575	3/4" x 3/4"	Steel
MPE 1075	1" x 3/4"	Steel
MPE 1010	1" x 1"	Steel

FEMALE PIPE SWIVEL ELBOW

FEMALE PIPE TO 90° FEMALE SWIVEL



PART #	SIZE	MATERIAL
FPE 2525	1/4" x 1/4"	Steel
FPE 2538	1/4" x 3/8"	Steel
FPE 3825	3/8" x 1/4"	Steel
FPE 3838	3/8" x 3/8"	Steel
FPE 3850	3/8" x 1/2"	Steel
FPE 5038	1/2" x 3/8"	Steel
FPE 5050	1/2" x 1/2"	Steel
FPE 5075	1/2" x 3/4"	Steel
FPE 7550	3/4" x 1/2"	Steel
FPE 7575	3/4" x 3/4"	Steel
FPE 1010	1" x 1"	Steel

HEX HEAD PLUG

SOLID MALE END TO PLUG, MALE END



PART #	SIZE	MATERIAL
HHP 12	1/8"	Steel
HHP 25	1/4"	Steel
HHP 38	3/8"	Steel
HHP 50	1/2"	Steel
HHP 75	3/4"	Steel
HHP 100	1"	Steel

HEX PIPE CAP

FEMALE PIPE TO CAP



PART #	SIZE	MATERIAL
HC 12	1/8"	Steel
HC 25	1/4"	Steel
HC 38	3/8"	Steel
HC 50	1/2"	Steel
HC 75	3/4"	Steel
HC 100	1"	Steel

SQUARE HEAD PIPE PLUG



PART #	SIZE	MATERIAL
SPP 12	1/8"	Steel
SPP 25	1/4"	Steel
SPP 38	3/8"	Steel
SPP 50	1/2"	Steel
SPP 75	3/4"	Steel
SPP 100	1"	Steel

JIC CAP PLUG



PART #	SIZE	MATERIAL
JC 12	JIC#2	Steel
JC 25	JIC#4	Steel
JC 30	JIC#5	Steel
JC 38	JIC#6	Steel
JC 50	JIC#8	Steel
JC 62	JIC#10	Steel
JC 75	JIC#12	Steel
JC 100	JIC#16	Steel

UNION PIPE TEES

MALE BY MALE BY MALE



PART #	SIZE	MATERIAL
UPT 12	1/8" x 1/8" x 1/8"	Steel
UPT 25	1/4" x 1/4" x 1/4"	Steel
UPT 38	3/8" x 3/8" x 3/8"	Steel
UPT 50	1/2" x 1/2" x 1/2"	Steel
UPT 75	3/4" x 3/4" x 3/4"	Steel
UPT 100	1" x 1" x 1"	Steel

FEMALE PIPE TEE

FEMALE BY FEMALE BY FEMALE



PART #	SIZE	MATERIAL
FPT 12	1/8" x 1/8" x 1/8"	Steel
FPT 25	1/4" x 1/4" x 1/4"	Steel
FPT 38	3/8" x 3/8" x 3/8"	Steel
FPT 50	1/2" x 1/2" x 1/2"	Steel
FPT 75	3/4" x 3/4" x 3/4"	Steel
FPT 100	1" x 1" x 1"	Steel

UNION PIPE TEE

FEMALE SWIVEL



PART #	SIZE	MATERIAL
UPTF 12	1/8" x 1/8" x 1/8"	Steel
UPTF 25	1/4" x 1/4" x 1/4"	Steel
UPTF 38	3/8" x 3/8" x 3/8"	Steel
UPTF 50	1/2" x 1/2" x 1/2"	Steel
UPTF 75	3/4" x 3/4" x 3/4"	Steel
UPTF 100	1" x 1" x 1"	Steel

FEMALE CROSS

FEMALE NPTF PIPE



PART #	SIZE	MATERIAL
FC 12	1/8" x 1/8" x 1/8" x 1/8"	Steel
FC 25	1/4" x 1/4" x 1/4" x 1/4"	Steel
FC 38	3/8" x 3/8" x 3/8" x 3/8"	Steel
FC 50	1/2" x 1/2" x 1/2" x 1/2"	Steel
FC 75	3/4" x 3/4" x 3/4" x 3/4"	Steel
FC 100	1" x 1" x 1" x 1"	Steel

FREE WORKING SWIVELS



MALE PIPE TO FEMALE PIPE			FEMALE PIPE TO FEMALE PIPE		
PART #	SIZE	MATERIAL	PART #	SIZE	MATERIAL
FS 2525	1/4" x 1/4"	Steel	FSF 2525	1/4" x 1/4"	Steel
FS 3838	3/8" x 3/8"	Steel	FSF 3838	3/8" x 3/8"	Steel
FS 5050	1/2" x 1/2"	Steel	FSF 5050	1/2" x 1/2"	Steel
FS 7575	3/4" x 3/4"	Steel	FSF 7575	3/4" x 3/4"	Steel
FS 1010	1" x 1"	Steel	FSF 1010	1" x 1"	Steel

CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.
TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.

MALE PIPE ELBOW

MALE NPT END TO 90° MALE NPT END, 30° CHAMFER MALE END



PART #	SIZE	MATERIAL
ME 2525	1/4" x 1/4"	Steel
ME 2538	1/4" x 3/8"	Steel
ME 3838	3/8" x 3/8"	Steel
ME 3850	3/8" x 1/2"	Steel
ME 5050	1/2" x 1/2"	Steel
ME 5075	1/2" x 3/4"	Steel
ME 7575	3/4" x 3/4"	Steel
ME 1010	1" x 1"	Steel

PIPE TEE

ONE FEMALE END, TWO MALE ENDS



PART #	SIZE	MATERIAL
PT 25	1/4" x 1/4" x 1/4"	Steel
PT 38	3/8" x 3/8" x 3/8"	Steel
PT 50	1/2" x 1/2" x 1/2"	Steel
PT 75	3/4" x 3/4" x 3/4"	Steel

MALE RUN TEE

TWO FEMALE ENDS, ONE MALE END



PART #	SIZE	MATERIAL
MPST 25	1/4" x 1/4" x 1/4"	Steel
MPST 38	3/8" x 3/8" x 3/8"	Steel
MPST 50	1/2" x 1/2" x 1/2"	Steel
MPST 75	3/4" x 3/4" x 3/4"	Steel
MPST 100	1" x 1" x 1"	Steel

STAINLESS STEEL

HEX NIPPLE

MALE NPT PIPE TO MALE NPT PIPE TAPERED ENDS, 30° CHAMFER



PART #	SIZE	MATERIAL
HN 12 SS	1/8" x 1/8"	316 Stainless Steel
HN 25 SS	1/4" x 1/4"	316 Stainless Steel
HN 38 SS	3/8" x 3/8"	316 Stainless Steel
HN 50 SS	1/2" x 1/2"	316 Stainless Steel
HN 75 SS	3/4" x 3/4"	316 Stainless Steel
HN 100 SS	1" x 1"	316 Stainless Steel

HEX REDUCING NIPPLE

MALE NPT PIPE TO MALE NPT PIPE TAPERED ENDS, 30° CHAMFER



PART #	SIZE	MATERIAL
HRN 1225 SS	1/8" x 1/4"	316 Stainless Steel
HRN 2538 SS	1/4" x 3/8"	316 Stainless Steel
HRN 2550 SS	1/4" x 1/2"	316 Stainless Steel
HRN 3850 SS	3/8" x 1/2"	316 Stainless Steel
HRN 3875 SS	3/8" x 3/4"	316 Stainless Steel
HRN 5075 SS	1/2" x 3/4"	316 Stainless Steel
HRN 7510 SS	3/4" x 1"	316 Stainless Steel

HEX REDUCING BUSHING

FEMALE PIPE TO MALE NPT PIPE, 30° CHAMFER MALE END



PART #	SIZE	MATERIAL
HRB 1225 SS	1/8" x 1/4"	316 Stainless Steel
HRB 2538 SS	1/4" x 3/8"	316 Stainless Steel
HRB 3850 SS	3/8" x 1/2"	316 Stainless Steel
HRB 5075 SS	1/2" x 3/4"	316 Stainless Steel
HRB 7510 SS	3/4" x 1"	316 Stainless Steel

MALE ADAPTER UNION

MALE NPT PIPE TO FEMALE SWIVEL



PART #	SIZE	MATERIAL
MFA 2525 SS	1/4" x 1/4"	316 Stainless Steel
MFA 2538 SS	1/4" x 3/8"	316 Stainless Steel
MFA 3825 SS	3/8" x 1/4"	316 Stainless Steel
MFA 3838 SS	3/8" x 3/8"	316 Stainless Steel
MFA 3850 SS	3/8" x 1/2"	316 Stainless Steel
MFA 5050 SS	1/2" x 1/2"	316 Stainless Steel
MFA 7575 SS	3/4" x 3/4"	316 Stainless Steel

FEMALE ADAPTER UNION

FEMALE PIPE TO FEMALE SWIVEL



PART #	SIZE	MATERIAL
FA 2525 SS	1/4" x 1/4"	316 Stainless Steel
FA 3838 SS	3/8" x 3/8"	316 Stainless Steel

PIPE ADAPTER

MALE NPT PIPE TO FEMALE PIPE, 30° CHAMFER



PART #	SIZE	MATERIAL
PA 1212 SS	1/8" x 1/8"	316 Stainless Steel
PA 1225 SS	1/8" x 1/4"	316 Stainless Steel
PA 1238 SS	1/8" x 3/8"	316 Stainless Steel
PA 2525 SS	1/4" x 1/4"	316 Stainless Steel
PA 2538 SS	1/4" x 3/8"	316 Stainless Steel
PA 3838 SS	3/8" x 3/8"	316 Stainless Steel
PA 3850 SS	3/8" x 1/2"	316 Stainless Steel
PA 3875 SS	3/8" x 3/4"	316 Stainless Steel
PA 5075 SS	1/2" x 3/4"	316 Stainless Steel
PA 5010 SS	1/2" x 1"	316 Stainless Steel

HEX PIPE COUPLING

FEMALE PIPE TO FEMALE PIPE



PART #	SIZE	MATERIAL
HPC 1212 SS	1/8" x 1/8"	316 Stainless Steel
HPC 1225 SS	1/8" x 1/4"	316 Stainless Steel
HPC 2525 SS	1/4" x 1/4"	316 Stainless Steel
HPC 2538 SS	1/4" x 3/8"	316 Stainless Steel
HPC 3838 SS	3/8" x 3/8"	316 Stainless Steel
HPC 3850 SS	3/8" x 1/2"	316 Stainless Steel
HPC 5050 SS	1/2" x 1/2"	316 Stainless Steel
HPC 7575 SS	3/4" x 3/4"	316 Stainless Steel
HPC 7510 SS	3/4" x 1"	316 Stainless Steel

CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.
TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.

FEMALE PIPE TEE

FEMALE PIPE BY FEMALE PIPE BY FEMALE PIPE



PART #	SIZE	MATERIAL
FPT 25 SS	1/4" x 1/4" x 1/4"	316 Stainless Steel
FPT 38 SS	3/8" x 3/8" x 3/8"	316 Stainless Steel
FPT 50 SS	1/2" x 1/2" x 1/2"	316 Stainless Steel
FPT 75 SS	3/4" x 3/4" x 3/4"	316 Stainless Steel

UNION PIPE TEE

MALE NPT PIPE BY MALE NPT PIPE BY MALE NPT PIPE, 30° CHAMFER



PART #	SIZE	MATERIAL
UPT 25 SS	1/4" x 1/4" x 1/4"	316 Stainless Steel
UPT 38 SS	3/8" x 3/8" x 3/8"	316 Stainless Steel

MALE PIPE ELBOW

90° MALE NPT PIPE TO MALE NPT PIPE, 30° CHAMFER



PART #	SIZE	MATERIAL
ME 1225 SS	1/8" x 1/4"	316 Stainless Steel
ME 2525 SS	1/4" x 1/4"	316 Stainless Steel
ME 2538 SS	1/4" x 3/8"	316 Stainless Steel
ME 3838 SS	3/8" x 3/8"	316 Stainless Steel
ME 5050 SS	1/2" x 1/2"	316 Stainless Steel
ME 7575 SS	3/4" x 3/4"	316 Stainless Steel
ME 1010 SS	1" x 1"	316 Stainless Steel

FEMALE PIPE ELBOW

90° FEMALE PIPE TO FEMALE PIPE RIGID



PART #	SIZE	MATERIAL
FE 2525 SS	1/4" x 1/4"	316 Stainless Steel
FE 2538 SS	1/4" x 3/8"	316 Stainless Steel
FE 5050 SS	1/2" x 1/2"	316 Stainless Steel
FE 7575 SS	3/4" x 3/4"	316 Stainless Steel

MALE PIPE SWIVEL ELBOW

90° MALE PIPE TO FEMALE SWIVEL, 30° CHAMFER



PART #	SIZE	MATERIAL
MPE 2525 SS	1/4" x 1/4"	316 Stainless Steel
MPE 3838 SS	3/8" x 3/8"	316 Stainless Steel
MPE 5050 SS	1/2" x 1/2"	316 Stainless Steel
MPE 7575 SS	3/4" x 3/4"	316 Stainless Steel

MALE/FEMALE PIPE ELBOW

90° MALE NPT PIPE TO FEMALE PIPE, 30° CHAMFER



PART #	SIZE	MATERIAL
MFE 2525 SS	1/4" x 1/4"	316 Stainless Steel
MFE 3838 SS	3/8" x 3/8"	316 Stainless Steel
MFE 5050 SS	1/2" x 1/2"	316 Stainless Steel
MFE 7575 SS	3/4" x 3/4"	316 Stainless Steel

HEX HEAD PLUG

MALE END



PART #	SIZE	MATERIAL
HHP 25 SS	1/4"	316 Stainless Steel
HHP 38 SS	3/8"	316 Stainless Steel

MALE CONNECTOR

MALE JIC TO MALE PIPE, 30° CHAMFER



PART #	SIZE	MATERIAL
HNJ 0425 SS	JIC#4 x 1/4"	316 Stainless Steel
HNJ 0525 SS	JIC#5 x 1/4"	316 Stainless Steel

FEMALE PIPE SWIVEL ELBOW

90° FEMALE PIPE TO FEMALE SWIVEL



PART #	SIZE	MATERIAL
FPE 7575 SS	3/4" x 3/4"	316 Stainless Steel

MALE RUN TEE

TWO FEMALE ENDS, ONE MALE NPT END, 30° CHAMFER



PART #	SIZE	MATERIAL
MPST 25 SS	1/4" x 1/4" x 1/4"	316 Stainless Steel

CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.
TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.

ADAPTER KIT

STARTER ASSORTMENT OF ADAPTERS



PART #	QTY	SIZE	SEE PG.
HN 25	24	1/4" x 1/4"	46
HN 38	9	3/8" x 3/8"	46
HN 50	3	1/2" x 1/2"	46
HRN 2538	10	1/4" x 3/8"	46
HRN 3850	4	3/8" x 1/2"	46
FPT 25	5	1/4" x 1/4" x 1/4"	53
MFA 2525	4	1/4" x 1/4"	48
MFA 2538	4	1/4" x 3/8"	48
HC 25	6	1/4"	49
HC 38	4	3/8"	49
HC 50	2	1/2"	49
UPT 25	2	1/4" x 1/4" x 1/4"	50
FA 2525	4	1/4" x 1/4"	52
FA 3838	4	3/8" x 3/8"	52
HRB 2538	4	1/4" x 3/8"	47
HRB 3850	4	3/8" x 1/2"	47
PA 2538	2	1/4" x 1/4"	52

Ball Valves

If you need ball valves that offer the same quality as the CRP hoses in your applications and installations, look no further. The male and female ball valve assemblies shown below work with paint, petroleum-based hydraulic fluids, fuel oil, and air.

CRP's male-thread ball valves use carbon steel for the body, hard chrome plated carbon steel for the ball, and zinc plated steel for the stem. Connections are male NPT, full bore, and the valves are rated to a working pressure of 7,500 PSI. Our female-thread ball valves have carbon steel or stainless steel bodies, hard chrome plated carbon steel or stainless steel balls, zinc plated steel or stainless steel stems, and Viton or Teflon seals. Connection is female NPT, full bore. For working pressures, please see chart below.

If you require other ball valve construction types, talk to a CRP service specialist who will be happy to discuss the other options available.

BALL VALVES MALE THREADS

BODY: FORGED CARBON STEEL STEM: FORGED CARBON STEEL
BALL: CHROME PLATED STEEL



PART #	SIZE	CONNECTIONS	WORKING PRESSURE	BALL SEALS	STEM SEALS
BV 2525	1/4" x 1/4"	Male NPT	7,500 psi	Delrin	Viton
BV 3838	3/8" x 3/8"	Male NPT	7,500 psi	Delrin	Viton

BALL VALVES FEMALE THREADS

BODY: FORGED CARBON STEEL STEM: FORGED CARBON STEEL
BALL: CHROME PLATED STEEL



PART #	SIZE	CONNECTIONS	WORKING PRESSURE	BALL SEALS	STEM SEALS
BVF 2525	1/4" x 1/4"	Female NPT	7,000 psi	Delrin	Viton
BVF 3838	3/8" x 3/8"	Female NPT	7,000 psi	Delrin	Viton
BVF 5050	1/2" x 1/2"	Female NPT	7,000 psi	Delrin	Viton
BVF 7575	3/4" x 3/4"	Female NPT	4,500 psi	Delrin	Viton
BVF 1010	1" x 1"	Female NPT	4,500 psi	Delrin	Viton
BVF 2525 T	1/4" x 1/4"	Female NPT	4,500 psi	Viton	Teflon
BVF 3838 T	3/8" x 3/8"	Female NPT	4,500 psi	Viton	Teflon
BVF 5050 T	1/2" x 1/2"	Female NPT	4,500 psi	Viton	Teflon
BVF 7575 T	3/4" x 3/4"	Female NPT	3,600 psi	Viton	Teflon
BVF 1010 T	1" x 1"	Female NPT	3,600 psi	Viton	Teflon

SPARE HANDLES

INCLUDES HANDLE, SPARE SCREW AND WASHER



PART #	SIZE	MATERIAL
BV 25 HAND	1/4"	Steel
BV 38 HAND	3/8"	Steel
BV 50 HAND	1/2"	Steel
BV 75 HAND	3/4"	Steel

BALL VALVE REPAIR KITS

INCLUDES ONE BALL, SEALS AND SEATS



PART #	FITS	SIZE	MATERIAL
BV 25K	BV2525, BVF2525	1/4"	Chrome Steel Ball – Delrin & Teflon Seals
BV 38K	BV3838, BVF3838	3/8"	Chrome Steel Ball – Delrin & Teflon Seals
BV 50K	BVF5050	1/2"	Chrome Steel Ball – Delrin & Teflon Seals
BV 75K	BVF7575	3/4"	Chrome Steel Ball – Delrin & Teflon Seals
BV 100K	BVF1010	1"	Chrome Steel Ball – Delrin & Teflon Seals
BV 25KT	BVF2525T	1/4"	Stainless Steel Ball – Viton & Teflon Seals
BV 38KT	BVF3838T	3/8"	Stainless Steel Ball – Viton & Teflon Seals
BV 50KT	BVF5050T	1/2"	Stainless Steel Ball – Viton & Teflon Seals
BV 75KT	BVF7575T	3/4"	Stainless Steel Ball – Viton & Teflon Seals
BV 100KT	BVF1010T	1"	Stainless Steel Ball – Viton & Teflon Seals

CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.

TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.

Hose Jacketing

CRP is proud to offer Expando PT hose jacketing. Expando PT is a self-fitting protective oversleeve, with expandable braid construction, designed to offer maximum resistance to abrasion and impact damage. Its open weave construction allows easy identification of contents. An additional advantage offered by these lightweight oversleeves is that each size fits several diameters.

Expando PT is easy to apply, has an operating temperature range from -40° F to +125°F, and is up to 4 times more abrasion resistant than competitive products. Additional features like flexibility, choice of colors, and resistance to most industrial fluids round out Expando PT's advantages.

HOSE JACKETING

SELF-FITTING PROTECTIVE OVERSLEEVE



PART # (COLOR)	SLEEVE SIZE	EXPANDED SIZE	FEET PER SPOOL	WEIGHT PER 100 FT. (LBS.)
JACKET 012 (color)	1/8"	1/4"	2,000	0.16
JACKET 025 (color)	1/4"	7/16"	1,000	0.24
JACKET 050 (color)	1/2"	3/4"	500	0.77
JACKET 075 (color)	3/4"	1 1/4"	500	1.20
JACKET 125 (color)	1 1/4"	1 3/4"	250	1.60
JACKET 175 (color)	1 3/4"	2 3/4"	250	2.70
JACKET 200 (color)	2"	3 1/2"	250	3.30
JACKET 250 (color)	2 1/2"	4 1/2"	250	4.60

*Always specify hose jacket color when ordering.

Pressure Gauge

CRP's Pressure Gauge line up comes in a variety of pressure ranges, dial and connection sizes, and mounting configurations. For added durability and accuracy in more extreme environments, glycerine filled gauges are also available.

PRESSURE GAUGE

GLASS-FACED



PART #	PRESSURE RANGE (PSI)	CONNECTION (MALE)	MOUNT	DIAL DIAMETER	METAL FINISH	LIQUID FILLED
PG15-200B	0 to 15	1/8"	Back	2"	Black	No
PG30-150	0 to 30	1/8"	Bottom	1 1/2"	Black	No
PG60-200	0 to 60	1/4"	Bottom	2"	Black	No
PG60-200B	0 to 60	1/4"	Back	2"	Black	No
PG100-150	0 to 100	1/8"	Bottom	1 1/2"	Black	No
PG100-150B	0 to 100	1/8"	Back	1 1/2"	Black	No
PG100-200	0 to 100	1/4"	Bottom	2"	Black	No
PG100-200B	0 to 100	1/4"	Back	2"	Black	No
PG100-200-8	0 to 100	1/8"	Bottom	2"	Black	No
PG160-200	0 to 160	1/4"	Bottom	2"	Black	No
PG160-200B	0 to 160	1/4"	Back	2"	Black	No
PG200-150	0 to 200	1/8"	Bottom	1 1/2"	Black	No
PG200-150B	0 to 200	1/8"	Back	1 1/2"	Black	No
PG200-200	0 to 200	1/4"	Bottom	2"	Black	No
PG100-250	0 to 100	1/4"	Bottom	2 1/2"	Stainless	Yes
PG300-250	0 to 300	1/4"	Bottom	2 1/2"	Stainless	Yes
PG1000-250	0 to 1,000	1/4"	Bottom	2 1/2"	Stainless	Yes
PG1500-250	0 to 1,500	1/4"	Bottom	2 1/2"	Stainless	Yes
PG2000-250	0 to 2,000	1/4"	Bottom	2 1/2"	Stainless	Yes
PG3000-250	0 to 3,000	1/4"	Bottom	2 1/2"	Stainless	Yes
PG5000-250	0 to 5,000	1/4"	Bottom	2 1/2"	Stainless	Yes
PG6000-250	0 to 6,000	1/4"	Bottom	2 1/2"	Stainless	Yes
PG10K-250	0 to 10,000	1/4"	Bottom	2 1/2"	Stainless	Yes

PRESSURE TEST GAUGE KIT

INCLUDES PSI GAUGE, TEE, SWIVEL AND HEX NIPPLE



PART #	PRESSURE RANGE (PSI)	CONNECTION (MALE)	MOUNT	DIAL DIAMETER	METAL FINISH	LIQUID FILLED
PG5000-KIT	0 to 5,000	1/4"	Bottom	2 1/2"	Stainless (Gauge) Plated Steel (Fittings)	Yes

CUSTOM SIZES AND OTHER COUPLING CAPABILITIES AVAILABLE ON ALL HOSES.
TO PLACE AN ORDER OR SPEAK WITH A CRP REPRESENTATIVE, CALL 800-526-4066.

Quick Disconnects

The fastest and simplest way to connect and disconnect hoses are these quick couplers. For use in spray applications, the working pressure rating for the 1/4" coupler is 5,000 psi; for the 3/8" option, 4,000 psi; and for the 1/2", 4,000 psi. Viton O-rings allow use with most paints and solvents. We can also source non-standard couplers, call for details.

QUICK COUPLERS



FEMALE ENDS		MALE ENDS	
PART #	SIZE	PART #	SIZE
QC 25F	1/4"	QC 25M	1/4"
QC 38F	3/8"	QC 38M	3/8"
QC 50F	1/2"	QC 50M	1/2"

NIPPLES



FEMALE ENDS		MALE ENDS	
PART #	SIZE	PART #	SIZE
QC 25FN	1/4"	QC 25MN	1/4"
QC 38FN	3/8"	QC 38MN	3/8"
QC 50FN	1/2"	QC 50MN	1/2"

DOUBLE SHUT OFF SERIES

ALL FEMALE ENDS



QUICK COUPLERS		NIPPLES	
PART #	SIZE	PART #	SIZE
QCDS 25F	1/4"	QCDS 25FN	1/4"
QCDS 38F	3/8"	QCDS 38FN	3/8"

High Pressure Hose Safety

CRP Industrial is very concerned about your safety when working with High Pressure Hose and related equipment. We have compiled this list of best practices for your reference and invite you to suggest any other safety measures that you have found valuable in your experience with high pressure hose and equipment.

Best Practices for High Pressure Hose Safety

- Stay within the stated working pressure of hose or equipment — never exceed this pressure.
- Work within the "minimum bend radius" guidelines suggested. Exceeding this radius could cause a kink that will lead to hose failure.
- Stay within recommended operating temperature limits of both hose and equipment. Higher temperatures increase pressure, which can cause failure.
- Inspect hoses prior to every use for signs of wear such as cuts, abrasions, coupling integrity, etc.
- Do not interline CRP hose with that of another manufacturer. Differences in manufacturing tolerances and quality standards could result in the failure of the weaker hose.
- Route hose away from areas of high temperature such as exhaust manifolds, heaters, or burners.
- Never run over hose with a vehicle or equipment, as this can compromise the integrity of the hose in a way that might not be visible.
- To avoid uncontrolled and potentially dangerous static discharges, be sure that all equipment is properly grounded.

If you have any comments or questions about these guidelines or hose safety in general, please call your CRP representative.